




# Technical Data Sheet

Customer:  
**Kaschke Göttingen**

Part designation:  
**SP-E 13/6**

Customer part no.:  
**SLNK363-5-3**

d:/bv/znt1864.dwg



Core / material / air gap / AL	<b>E13/6 K2006 or equiv.</b>	
Nominal inductance	<b>LI= 1,6mH ±10%</b>	
maximum transmissible power	<b>4W</b>	
Working frequency	<b>132KHz</b>	
Transformation ratio	<b>135:23:11</b>	
dielectric strength (50Hz/2s)	<b>Prim - Sec: 3,75KV</b>	
Nominal Current		
Design in comp. with standard	<b>S98</b>	
Working / storage temperature	<b>-25 °C- +120 °C</b>	<b>-25 °C- +85 °C</b>
Miscellaneous		
switcher	<b>Link363-universal</b>	

Remarks : a.) marking

Measuring device of L: **W&K 3260A**

Measuring conditions of L: **50mV/10kHz/25 °C**

Measured quantity	Unit	No. 1	No. 2	No. 3	No. 4	No. 5

Responsible person:

**Markus Häpe**

Date:

**20.03.2008**

Design regulation no:

**096.840**

Index:

**00**

**PLEASE GIVE US YOUR WRITTEN RELEASE**

Date

Signature